HellermannTyton

Article Number: 184-13005



Description: Slotted Cable and Wiring Duct, High-Density, 1" x 3", Non-Adhesive, PVC, Gray, 120 ft/carton

Base Data		
	Local Order Number	184-13005
	Туре	SLHD1X3
	Color	Gray (GY)
	Features and Benefits	 Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance. Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation. Mounting holes are uniform in size to the solid and slotted wall duct, but are offered every 2 inches to accommodate compact designs and ease installation.
	Quantity Per	carton
	Product Description	Pro-Duct high density, slotted wiring duct features narrow fingers, a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.
	Technical Description	Non-Adhesive
	Short Description	Slotted Cable and Wiring Duct, High-Density, 1" x 3", Non-Adhesive, PVC, Gray, 120 ft/carton
Product Dimensions		
	Length L (Imperial)	6.0ft
	Length L (Metric)	1.83m
	Width W (Imperial)	1.0"
	Width W (Metric)	25.4mm
	Width W2 (Imperial)	1.0"
	Width W2 (Metric)	25.4mm
	Width W3 (Imperial)	0.16"
	Width W3 (Metric)	4.1mm
	Width W4 (imperial)	0.4"
	Width W4 (metric)	10.2mm
	Width W5 (imperial)	2.6"
	Width W5 (metric)	66.0mm

184-13005

HellermannTyton

	ight H (Imperial)	3.07"
Dimensions	ight H (Metric)	77.9mm
Μοι	unting Hole Centers (Imperial)	2.0"
Material and Specifications		
Mat	terial	Polyvinylchloride (PVC)
Mat	terial Shortcut	PVC
Flar	mmability	self-extinguishing
Ope	erating Temperature	+122°F (+50°C)
ROI	HS Compliant	Yes
Cer	rtification/Specification	CSA
UL	Recognized (US)	Yes
Logistic and Packaging		
Pac	ckage Quantity (Imperial)	120ft
Pac	ckage Quantity (Metric)	36.6m
Cus	stoms Number(Schedule B)	3925900000