



**PIN ASSIGNMENT:**

P1	P2	P3	COLOR
1	1		RED
2		1	WHITE
3	2	2	DRAIN(RED)
			DRAIN(WHITE)

- Material:**
- Cable: NOUS [(10/0.10)+S(28/0.10)]\*2F
    - PVC-40P Jacket Black
    - OD 2.8\*5.6MM
    - L=1500±10MM
  - P1 Connector: 3.5ST Male
    - Tray 6.0MM L=26MM
    - Mold Type Ni-Plated insulator color Black
  - P2 Connector: RCA Plug Male
    - Blossom Type Ni-Plated insulator color Brown
    - In Jacket: Clear LD-PE
    - Out Jacket: PVC-40P Red
  - P3 Connector: RCA Plug Male
    - Blossom Type Ni-Plated insulator color Brown
    - In Jacket: Clear LD-PE
    - Out Jacket: PVC-40P White
  - Tube: Heat Shrink Black OD1.5\*10MM
  - S/R: Black PVC 40P
- Electrical:**
- 100% Short, open, miswire test
  - Conduct resistance: 5Ω (Max)
  - Insulation resistance: 5MΩ (Min)
  - Dielectric test: 300V DC

Unit: MM



Scale	1:1									Name
TOLERANCE						Drawn	01.03.12			Chappell
X.X	±0.40					Approved				
X.XX	±0.25									
X.XXX	±0.15									
Angle	±3°									
Modification					Date	Name				



Item No.	<b>AK243-015</b>
Title	Stereo Connection Cable - 1.5 Meters, 3.5ST Male <=> 2x RCA Male
Drawing No.	
Replace	rev00
Sheet	