## **HellermannTyton**



Article Number: 170-03038

Description: Braided Sleeving, Split Wrap, .75" Dia, PET, Black, 50

ft/reel

| Base Data                      |                                 |  |
|--------------------------------|---------------------------------|--|
|                                | Local Order Number              | 170-03038  |
|                                |                                 |  |
|                                | Туре                            | BSPSW340   |
|                                | Color                           | Black (BK)   |
|                                | Features and Benefits           | <ul> <li>Split wrap design installs quickly, saving assembly time and future accessibility without disassembly.</li> <li>Unique construction retains shape and rigidity throughout unrolling.</li> <li>Easy open design allows quick assembly, future access, and ability to apply protective sleeving post assembly or post installation situations.</li> </ul> |
|                                | Quantity Per                    | reel   |
|                                | Product Description             | A lateral split, semi-rigid and flame retardant braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires.    |
|                                | Short Description               | Braided Sleeving, Split Wrap, .75" Dia, PET, Black, 50 ft/reel   |
| Product<br>Dimensions          |                                 |  |
|                                | Length L (Imperial)             | 50.0ft   |
|                                | Length L (Metric)               | 15.2m  |
|                                | Reel Length (imperial)          | 50.0ft   |
|                                | Bundle Diameter Max. (Imperial) | 0.75"  |
|                                | Bundle Diameter Max. (Metric)   | 19.1mm   |
|                                | Nominal Diameter (Imperial)     | 3/4"   |
|                                | Nominal Diameter (Metric)       | 19.1mm   |
| Material and<br>Specifications |                                 |  |
|                                | Material                        | Polyester (PET)  |
|                                | Material Shortcut               | PET  |
|                                | Flammability                    | UL 94 V0   |
|                                | Operating Temperature           | -94°F to +248°F (-70°C to +125°C)  |

generated on: 4/28/2017

## 170-03038



| Material and<br>Specifications | ROHS Compliant                | Yes        |
|--------------------------------|-------------------------------|------------|
|                                | UL Recognized (US and Canada) | Yes        |
| Logistic and Packaging         |                               |            |
|                                | Package Quantity (Imperial)   | 50ft       |
|                                | Package Quantity (Metric)     | 15.24m     |
|                                | Customs Number(Schedule B)    | 3926909987 |
|                                | Weight (imperial)             | 0.8lbs     |
|                                | Weight (Metric)               | 0.36kg     |

generated on: 4/28/2017