

169-60009



Article Number: 169-60009

Description: Convoluted Tubing, Slit, .25" Dia, PA6, Black with Gray Stripe, 3200 ft/carton

Base Data	Local Order Number	CTN140STD
	Type	CTN140
	Color	Black with Gray Stripe (BKSTGY)
	Features and Benefits	<ul style="list-style-type: none"> <li>• Durable tubing provides protection of wire harness from friction, vibration, fraying and puncture</li> <li>• Tubing protects cables and wires against automotive fluids, vibration wear</li> <li>• Weather resistant material provides protection against water, snow, ice, and the effects of heat, cold, and sunlight</li> </ul>
	Quantity Per	carton
	Product Description	HellermannTyton's Convoluted Tubing, also known as Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offer's excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.
	Technical Description	Convoluted Tubing, Slit, 1/4" Dia., PA6, Black w/Gray Stripe
	Short Description	Convoluted Tubing, Slit, .25" Dia, PA6, Black with Gray Stripe, 3200 ft/carton
	Product Dimensions	Length L (Imperial)
Length L (Metric)		975.4m
Inner Diameter D (Imperial)		0.276"
Inner Diameter D (metric)		7.01mm
Diameter D (imperial)		0.398"
Diameter D (metric)		10.11mm
Diameter D2 (imperial)		0.276"
Diameter D2 (metric)		7.01mm
Outside Diameter D (imperial)		0.398"
Outside Diameter D (metric)		10.11mm
Nominal Diameter (Imperial)		1/4"

169-60009

**HellermannTyton**

Product Dimensions	Nominal Diameter (Metric)	6.35mm
	Wall Thickness WT (Imperial)	.004"
	Wall Thickness WT (Metric)	0.102mm
Material and Specifications		
	Material	Polyamide 6 (PA6)
	Material Shortcut	PA6
	Flammability	UL 94 HB
	Operating Temperature	-40°F to +300°F (-40°C to +149°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	3200ft
	Package Quantity (Metric)	975.4m
	Customs Number(Schedule B)	3926909987