

170-03035

Article Number: 170-03035

Description: Braided Sleeving, Expandable, Fray Resistant, .25" Dia, PET, Black, 100 ft/reel



| | | |
|---------------------------------|-----------------------|--|
| Base Data | Local Order Number | 170-03035 |
| | Type | BSPSC140 |
| | Color | Black (BK) |
| | Features and Benefits | <ul style="list-style-type: none"> • Cuts with scissors without fraying ends enables field installations without need for hot knife. • Material construction offers excellent abrasion and cut-through protection as well as inertness to common chemicals and fungus. • Expands to 150% of easy installation and reduced assembly time requirements. |
| | Quantity Per | reel |
| | Product Description | A versatile and economical general purpose braided sleeving that resists fraying when cut with ordinary scissors. |
| | Short Description | Braided Sleeving, Expandable, Fray Resistant, .25" Dia, PET, Black, 100 ft/reel |
| | Product Dimensions | Length L (Imperial) |
| Length L (Metric) | | 30.48m |
| Reel Length (imperial) | | 100.0ft |
| Bundle Diameter Min. (Imperial) | | 0.156" |
| Bundle Diameter Min. (Metric) | | 4.0mm |
| Bundle Diameter Max. (Imperial) | | 0.437" |
| Bundle Diameter Max. (Metric) | | 11.1mm |
| Nominal Diameter (Imperial) | | 1/4" |
| Nominal Diameter (Metric) | | 6.4mm |
| Material and Specifications | | Material |
| | Material Shortcut | PET |
| | Flammability | UL 94 V0 |
| | | |

170-03035



| | | |
|-----------------------------|-------------------------------|-----------------------------------|
| Material and Specifications | Operating Temperature | -94°F to +248°F (-70°C to +125°C) |
| | ROHS Compliant | Yes |
| | UL Recognized (US and Canada) | Yes |
| Logistic and Packaging | | |
| | Package Quantity (Imperial) | 100ft |
| | Package Quantity (Metric) | 30.48m |
| | Customs Number(Schedule B) | 3926909987 |
| | Weight (imperial) | 0.46lbs |
| | Weight (Metric) | 0.21kg |