HellermannTyton



Article Number: 184-11010

Description: Slotted Cable and Wiring Duct, High-Density, 1" x 1.5", Non-Adhesive, PVC, Gray, 120 ft/carton

| Base Data | | |
|-----------------------|-----------------------|---|
| | | |
| | Local Order Number | 184-11010 |
| | Туре | SLHD1X1.5 |
| | Color | Gray (GY) |
| | Features and Benefits | Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance. Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation. Mounting holes are uniform in size to the solid and slotted wall duct, but are offered every 2 inches to accommodate compact designs and ease installation. |
| | Quantity Per | carton |
| | Product Description | Pro-Duct high density, slotted wiring duct features narrow fingers, a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated. |
| | Technical Description | Non-Adhesive |
| | Short Description | Slotted Cable and Wiring Duct, High-Density, 1" x 1.5", Non-Adhesive, PVC, Gray, 120 ft/carton |
| Product Dimensions | | |
| | Length L (Imperial) | 6.0ft |
| | Length L (Metric) | 1.83m |
| | Width W (Imperial) | 1.0" |
| | Width W (Metric) | 25.4mm |
| | Width W2 (Imperial) | 1.0" |
| | Width W2 (Metric) | 25.4mm |
| | Width W3 (Imperial) | 0.16" |
| | Width W3 (Metric) | 4.1mm |
| | Width W4 (imperial) | 0.4" |
| | Width W4 (metric) | 10.2mm |
| | Width W5 (imperial) | 1.19" |
| | Width W5 (metric) | 30.2mm |

184-11010

HellermannTyton

| Product Dimensions | Height H (Imperial) | 1.57" |
|--------------------------------|----------------------------------|-------------------------|
| | Height H (Metric) | 39.9mm |
| | Mounting Hole Centers (Imperial) | 2.0" |
| Material and Specifications | | |
| | Material | Polyvinylchloride (PVC) |
| | Material Shortcut | PVC |
| | Flammability | self-extinguishing |
| | Operating Temperature | +122°F (+50°C) |
| | ROHS Compliant | Yes |
| | Certification/Specification | CSA |
| | UL Recognized (US) | Yes |
| Logistic and Packaging | | |
| | Package Quantity (Imperial) | 120ft |
| | Package Quantity (Metric) | 36.6m |
| | Customs Number(Schedule B) | 3925900000 |
| | | |