







## NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL:

HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER

2. MODIFICATIONS: END CAP

## 3. SPECIFICATIONS:

- 3.1 CURRENT RATING: 13 AMPS
- 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
- 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
- 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
- 3.5 MOISTURE RESISTANCE: IP67 (MATED CONDITION)
- 3.6 MATING CYCLE DURABILITY: 100 CYCLES
- 3.7 RoHS COMPLIANT
- 4. MATING PART: AT06-3S\* RECEPTACLE (\* = MODIFICATIONS AND COLORS)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.
- 6 CONTACT SIZE AND REAR SEAL WIRE RANGE:

CONTACT	MIN. INSUL	MAX. INSUL	TYPICAL
SIZE	O.D.	O.D.	WIRE RANGE
16	2.24 mm (.088 in)	3.68 mm (.145 in)	14 - 20 AWG

PART NUMBER CHART					
COLOR	PART NUMBER				
GREY	AT04-3P-EC01				
BLACK	AT04-3P-EC01BLK				
BLUE	AT04-3P-EC01BLU				
BROWN	AT04-3P-EC01BRN				
GREEN	AT04-3P-EC01GRN				
RED	AT04-3P-EC01RED				
WHITE	AT04-3P-EC01WHT				
YELLOW	AT04-3P-EC01YEL				

REVISIONS							
REV	ECO	DESCRIPTION	DATE	BY	APPR		
А3	-	RELEASE NEW DWG FORMAT	02JAN14	JARRY			

RECEPTACLE, 3 PIN, AT SERIES, END CAP

AT04-3P-EC01XXX

3



