

170-03052

Article Number: 170-03052



Description: Braided Sleeving, Resin Coated Fiberglass, .75" Dia, GF, Black, 200 ft/bulk reel

Base Data	Local Order Number	170-03052
	Type	BSHTFG340B
	Color	Black (BK)
	Features and Benefits	<ul style="list-style-type: none"> • An extremely tough sleeving material which provides thermal protection up to 1,200°F. • Sturdy construction maintains its tight structure under extreme shaking, scraping, pressure and varying temperature conditions. • Cuts easily with ordinary scissors for easy application. • UL VW-1 flammability rating for use in conditions requiring a very high degree of flame resistance.
	Product Description	An extremely high-temperature resistant sleeving designed to protect wires and cables subjected to continuous temperature variations, vibration, abrasion, and mechanical stress.
	Short Description	Braided Sleeving, Resin Coated Fiberglass, .75" Dia, GF, Black, 200 ft/bulk reel
Product Dimensions	Length L (Imperial)	200.0ft
	Length L (Metric)	61.0m
	Reel Length (imperial)	200.0ft
	Bundle Diameter Max. (Imperial)	1.125"
	Bundle Diameter Max. (Metric)	28.6mm
	Nominal Diameter (Imperial)	3/4"
	Nominal Diameter (Metric)	19.1mm
	Material and Specifications	Material
Material Shortcut		GF
Flammability		VW-1
Operating Temperature		-94°F to +1202°F (-70°C to +650°C)
ROHS Compliant		Yes

170-03052



Material and Specifications	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	200ft
	Package Quantity (Metric)	60.96m
	Customs Number(Schedule B)	7019901000
	Weight (imperial)	12.8lbs
	Weight (Metric)	5.81kg