HellermannTyton



Article Number: 181-22034

Description: Slotted Cable and Wiring Duct, 2" x 2", Adhesive, PVC, White, 120 ft/carton

Base Data		
	Local Order Number	181-22034
	Туре	SLA2X2
	Color	White (WH)
	Features and Benefits	 Strong fingers prevent unwanted breaking. Fingers are easily deflected outward, allowing ready positioning of the wires within the slotted wall duct. Restricted opening prevents unintended removal of wires and permits any individual wire to be traced without disconnection.
	Quantity Per	carton
	Product Description	Pro-Duct slotted wall wiring duct features break-away fingers which provide additional access for wire leads. Each section of the duct is provided with two score lines. The upper score line is used to break away fingers when a wider opening is required. The lower score line allows the sidewall to be smoothly cut for joints and "T's".
	Technical Description	Adhesive
	Short Description	Slotted Cable and Wiring Duct, 2" x 2", Adhesive, PVC, White, 120 ft/carton
Product Dimensions		
	Length L (Imperial)	6.0ft
	Length L (Metric)	1.83m
	Width W (Imperial)	2.0"
	Width W (Metric)	50.8mm
	Width W2 (Imperial)	2.0"
	Width W2 (Metric)	50.8mm
	Width W3 (Imperial)	0.4"
	Width W3 (Metric)	10.2mm
	Width W4 (imperial)	1.0"
	Width W4 (metric)	25.4mm
	Width W5 (imperial)	1.6"
	Width W5 (metric)	40.6mm

181-22034

HellermannTyton

(imperial)	0.5"
(metric)	12.7mm
(Imperial)	2.07"
(Metric)	52.6mm
Hole Centers (Imperial)	4.0"
	Polyvinylchloride (PVC)
hortcut	PVC
lity	self-extinguishing
Temperature	+122°F (+50°C)
mpliant	Yes
on/Specification	UL
nized (US)	Yes
Quantity (Imperial)	120ft
Quantity (Metric)	36.6m
Number(Schedule B)	3925900000
	Imperial) Metric) Hole Centers (Imperial) hortcut lity Temperature mpliant on/Specification nized (US)